



LG13 Lock guard

- Designed for use on all type 161 cylindrical locks (ANSI 156.2 Series 2000) Monolock and Unilock
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point
- Non-handed
- 2 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel, 12 gauge steel

Dimensions

- 1-1/2" wide x 7" high
- Stud center to center: 4-1/2"

Available accessory items

- Security pin fasteners

Finishes - Steel

BHMA	Description	Substrate	Finish
600	Primed for paint	Steel	USP

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.



LG14 Lock guard - with electric strike

- Narrow design unit for use on rose or escutcheon 3-1/2" or less.
- For use with Von Duprin 6210 and 6211 electric strike.
- No exposed fasteners on face of unit.
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point.
- Non-handed
- 4 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel

Dimensions

- 2-9/16" wide x 9-1/2" high
- Stud center to center: 8-1/2" and 6-3/4"

Available accessory items

- Security pin fasteners

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.