


<b>A</b>	Hinges & pivots
<b>B42</b>	Pulls & plates
<b>C</b>	Flush bolts & coordinators
<b>D</b>	Latches, catches & bolts
<b>E</b>	Stops
<b>F</b>	Exterior hardware
<b>G</b>	Miscellaneous hardware



## 8302 Pull plate

### Certifications

- Meets ANSI A156.06

### Mounting

- Heavy duty mounting hardware exceeds industry standards
- 5/16-18 mounting hardware
- Specify door thickness. Standard mounting hardware for door thickness of 1-1/2" to 1-3/4" unless otherwise specified. Optional package available for 2" and 2-1/4" thick doors.
- Comes standard with thru-bolt screws and decorative washers.
- Optional mounting hardware available (see general information section for details) F, G, I, J, L
- Mounting hardware for other door thicknesses are available as engineering special, consult customer service.*
- Standard mounting package for plate
  - #6 X 5/8 oval head screws
- Optional TEK/TORX package
  - #6 X 5/8 Self-drilling, Self-tapping screws and
  - #6 X 5/8 Torx screws
- Plate prepped with 2 pull mounting holes spaced at 6", 8", or 10" center to center

### Widths and heights

- 3-1/2" X 15"
- 4" X 16"
- 6" X 16"

### Pull center to center

- 6"
- 8"
- 10"

### Finishes

- Available in Aluminum, Brass, and Stainless Steel substrates. See general information section for specific BHMA finish code, finish description, US finish code, and substrate information.
- Standard finishes available; 605, 606, 612, 613, 619, 625, 626, 626-AM, 628, 630, 630-AM, 643e/716, BLK
- Custom finishes are available as engineering special, consult customer service.*

### Additional information

- Specify PR when ordering a set of pulls for back to back mounting
- For one back to back machined pull, specify Js9l
- Custom widths, heights, and special cut-outs are available as engineering special, consult customer service.*