

8400 Commercial protection plates
8402 UL Commercial protection plates

- Door protection plates are available in .050" thick brass, stainless steel or aluminum; and 1/8" thick high impact polyethylene in clear or black.
- All plates, metal and plastic, come standard with four beveled edges and countersunk mounting holes (B-CS).
- Protection plates must be ordered in 1/2" increments. Available in other sizes, consult customer service
- For 8402 UL Plates, UL mark appears in upper right corner. Not available on plastic protection plates.

Certifications

- Meets ANSI A156.6 for J301
- UL protection plates certified to UL10C

Mounting

- Standard mounting package, 16 per pack
 - #6 X 5/8 oval head screws
- Optional TEK/TORX package, specify TK-TX
 - #6 X 5/8 Self-drilling, Self-tapping screws
 - #6 X 5/8 Torx screws

Finishes

- Aluminum 5005 Series, Brass C26800 Series, Stainless Steel 300 Series, Plastic

| BHMA | Description | Substrate | Finish | Max sizes |
|-------|------------------------|-----------------|--------|-----------|
| 605 | Bright Brass | Brass | US3 | 24"X48" |
| 606 | Satin Brass | Brass | US4 | 24"X48" |
| 612 | Satin Bronze | Brass | US10 | 24"X48" |
| 613 | Oil rubbed Bronze | Brass | US10B | 36"X48" |
| 619 | Satin Nickel | Brass | US15 | 24"X48" |
| 625 | Bright Chrome | Brass | US26 | 36"X48" |
| 626 | Satin Chrome | Brass | US26D | 24"X48" |
| 628 | Satin Aluminium | Aluminium | US28 | 48"X48" |
| 629 | Bright Stainless Steel | Stainless Steel | US32 | 48"X48" |
| 630 | Satin Stainless Steel | Stainless Steel | US32D | 48"X48" |
| 654 | Satin Stainless Steel | Stainless Steel | US32D | 48"X48" |
| BLK | Matte black | Stainless Steel | BLK | 24"X48" |
| P-BLK | Black | Plastic | P-BLK | 48"X48" |
| CLR | Clear | Plastic | CLR | 48"X48" |

- Custom finishes are available as engineering special, consult customer service.

Available options

- Specify B-NH for no mounting holes. (Not available on 8402. Available only with US32D, US32, US3, US4, US28, Clear, Black only)
- Specify B-NHA for no mounting holes with adhesive.
- Specify ERS prepped with extra row of screws.
- Special Cut-outs are available as engineering special, consult customer service.

Available accessory

- Gasket tape kit tape is recommended when using a brass plate on a metal door to reduce tarnishing from electrolytic oxidation. One tape pack will cover an the perimeters of a 8" x 34" kickplate. Order 8401 gasket tape.



Number of screw packs required by plate size (specify TEK Screws or TORK screws)

| | 22"-25" | 26"-33" | 34"-41" | 42"-48" |
|---------|---------|---------|---------|---------|
| 4"-8" | 1 | 1 | 1 | 1 |
| 9"-16" | 1 | 1 | 1 | 1 |
| 17"-24" | 1 | 1 | 1 | 2 |
| 25"-32" | 1 | 1 | 2 | 2 |
| 33"-40" | 1 | 2 | 2 | 2 |
| 41"-48" | 2 | 2 | 2 | 2 |

A
Hinges & pivots

B47
Pulls & plates

C
Flush bolts & coordinators

D
Latches, catches & bolts

E
Stops

F
Exterior hardware

G
Miscellaneous hardware