

2000 SERIES STANDARD DUTY SVR EXIT DEVICE



Specification

- ANSI:** Meets ANSI A156.3 - Grade 1 Standards
- UL Listings:** UL Listed for Panic Exit Hardware
3 Hour Fire Doors to 8'-0" x 10'-0" & LBR up to 8'-0" x 8'-0"
- ADA:** Meets ADA requirements ANSI A117.1 with Lever Trim
- Handing:** Easily Re- handed in the field - Shipped as RHR
- Construction:** Roll Formed Steel or Stainless Steel Channel & Steel Chassis
Steel or Stainless Steel Head Cover & End Cap
- Finishes:** Aluminum, Dark Bronze, Gold Painted & US32D
- Top Latch:** U Shaped Top Latch for Secure Engagement with strike
- Bottom Latch:** Drop Bolt Style Bottom Latch Secures into flat strike & hole in the floor
- Dogging:** 5/32" Hex Key Dogging Standard on Panic Exit Hardware
- Device Lengths:** 33" for 3'-0" wide doors and 42" for 3'-8" to 4'-0" wide doors
- Min. Door Width:** 33" device can be cut down to fit on 2'-8" wide door
42" device can be cut down to fit on 3'-4" wide door
- Door Heights:** 7"-0" Standard - Extended Top Rods available for up to 10'-0" tall doors
- Center Case Dim.:** 6" Height x 2 5/16" Wide x 2 1/2" Thick - 4" Minimum stile required
- Mechanism Case Dim.:** 1 5/8" Height x 1 13/16" Wide
 - Projection:** 2 1/2" Undogged - Push bar Neutral & 1 13/16" Dogged - Push bar Depressed
 - Fasteners:** Wood, machine & self tapping machine screws (F2000V includes thru bolts)
 - Alarmed Exits:** Exit Alarm Kit ALK-2000 available for new or existing devices
- Trim & Accessories:** Latch filler included, Exterior Trims, Shim Kits & other accessories available
- Under Cut:** 1/4" door under cut recommended for 1/4" threshold or no threshold openings
- Warranty:** Limited lifetime warranty