

0600 Pull Side Mounting

Application

- Cross corridor doors - swinging in the same direction
- Maximum door weight 250 lbs.
- Doors up to 4'0" (1219mm)

Features


- Pull side mount
- Non-handed
- Hold open range 85° - 145°
- Mounts on 2" header
- Adjustable spring surface closer
- Maximum reveal 1/8"
- Concealed switch disconnects hold open
- 2 year limited warranty

Compliance

- UL listed
- Compliant with ANSI/BHMA A156.8 and A156.15 standards
- BHMA certified 
- ANSI/C00111

Electrical Data

- 24VAC/DC 80ma
- 120VAC 17ma



0601 Push Side Mounting

Application

- Cross corridor doors – double egress – doors swinging in opposite directions
- Maximum door weight 250 lbs.
- Doors up to 4'0" (1219mm)

Features

- Push side mount
- Non-handed
- Hold open range 85° - 135°
- Doors may swing and hold at 180° by using special arm 550789*
- Mounts on 2" header
- Adjustable spring surface closer
- Maximum reveal 3-1/2"
- For reveals 3-1/2" - 5-1/2" use special arm 550789*
- Concealed switch disconnects hold open
- 2 year limited warranty


Compliance

- UL listed
- Compliant with ANSI/BHMA A156.8 and A156.15 standards
- BHMA certified 
- ANSI/C00231

Electrical Data

- 24VAC/DC 80ma
- 120VAC 17ma

* 550789 arm can only be used on push side applications. For use on double egress doors with reveals from 3-1/2" to 5-1/2" or on applications where doors need to swing to 180°



RIXSON®
ASSA ABLOY