

FALCON®

SC60A Series

Standard-duty, Grade 1 door control

Overview

When you need a dependable closer for a light or medium-duty commercial application like a small boutique or office, the Falcon SC60A Series fits perfectly. Designed for interior use with aluminum storefronts and mix use complexes, the SC60A Series offers ANSI Grade 1 durability backed by a ten-year warranty. Since the SC60A has the most common hole pattern in the industry, it's a versatile and easy choice for retrofit. The SC60A is another great example of how Falcon provides a solid product at a solid price.

Features and benefits:

- Single piece cast aluminum body
- Fully adjustable sizes 1-5
- Separate adjustable general speed, latch speed and backcheck
- Industry common hole pattern retrofittable to Norton 1600
- Non-handed for left- or right-swinging doors
- Heat treated pinion and steel piston
- Staked valves
- Universal screw pack, now including SRTs screws
- Meets ANSI A117.1
- Certified ANSI/BHMA A156.4, Grade 1
- Cover is UL approved for use in fire rated assemblies
- UL listed and compliant to UL10C and UBC 7-2 (1997)
- 10-year warranty



The right accessories for every job

The non-handed design of the SC60A Series, paired with its mounting position versatility, means you can install this closer just about anywhere depending on the needs of the door opening. A host of arm types and accessories make it easy to fit the demands of a variety of applications.



Regular



Hold open



Heavy-duty regular



Dead stop




Dead stop hold open



Spring-n-Stop




Spring-n-Stop hold open




Soffit shoe support

Provides anchorage for fifth screw used with soffit shoe where reveal is less than 3 1/16" (78mm).




Blade stop spacer

Required to lower parallel arm shoe to clear 1/2" (13mm) blade stop.




Auxiliary shoe

Requires a top rail of 7" (178mm). Optional shoe replaces PA shoe for parallel arm mounting of regular arm with overhead holder/stop.




Plate

Required for top jamb mounting where head frame is less than 1 3/4" (44mm).



Parallel arm plate

Required for parallel arm mounting where top rail is less than 4 3/8" (111mm) for PA, 4 1/4" (108mm) for HD and DS, measured from the top. Plate requires 2 3/8" (60mm) minimum top rail measure from stop.



Cover

No cover comes standard unless otherwise specified. Optional, non-handed, slim line plastic cover available when specified.

Available finishes



622
Matte black¹



689
Aluminum



695
Dark bronze



696
Brass

¹ Available on the standard cylinder, RWPA arm, HWP arm, and DS arm.

About Allegion

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit www.allegion.com.