



230 Sliding door edge pull

- 3/4" width allows installation on narrow as well as standard doors.
- Spring automatically returns lever flush with plate.
- Packaged with fasteners for wood applications

Certifications

- Meets ANSI/BHMA 156.14 D2801

Material substrate

- Made from solid brass.

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	B3
606	Satin brass	Brass	B4
609	Blackened Brass	Brass	B5
612	Satin bronze	Brass	B10
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
—	Aged bronze	Brass	B-643e/716

Dimensions

- 3-7/8" high x 3/4" wide



42 Pocket sliding door bolt

- Exclusive Ives design permits emergency release of bolt from outside the door.
- Spring activated design allows feather-touch action.
- Brass grommet supplied to cap release hole, protecting the door's finish.
- Packaged with fasteners for wood applications

Material substrate

- Made from wrought brass.

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	B3
606	Satin brass	Brass	B4
609	Blackened Brass	Brass	B5
612	Satin bronze	Brass	B10
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
—	Aged bronze	Brass	B-643e/716

Dimensions

- Overall size plate: 3-1/16" high x 1-5/32" wide
- Strike: 1" high x 3/4" wide
- Depth of mortise: 5/8"

Hinges & pivots

A

Pulls & plates

B63

Flush bolts & coordinators

C

Latches, catches & bolts

D

Stops

E

Exterior hardware

F

Miscellaneous hardware

G