

The Envoy Door

Exterior Polystyrene Core



Door Construction

- 18 gauge face sheets
- Polystyrene Core
- Galvanealed face sheets
- Mechanically interlocked edge seams
- 16 gauge inverted top and bottom channels
- Top flush closure cap
- 10 gauge hinge reinforcements
- Non-handed, furnished with hinge closing plates
- 16 gauge closer reinforcement
- 1-1/2 Hour Warnock Hersey fire label
- 1 year manufacturers warranty

Sizes

- 2668, 2868, 3068, 3468, 3668, 2670, 2870, 3070, 3470, 3670

Hardware Preparations

- 2-1/8" cylindrical lock (LC1)
- Cylindrical Lever lock (LL3)
- Mortise edge prep only (LM0)
- Mortise edge & escutcheon trim prep only (LM1)
- Rim panic reinforcement only (PR1)
- Cylindrical dead lock at 48" AFF only (DB)
- Plain lock edge (LPO)
- SDI/NAAMM hinge & lock locations

Packaging

- Palletized 20 doors per pallet with edge wrap
- 60 Door minimum per order from factory
- No minimum from Door Group Service Centers

Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com • www.cecodoor.com

Ceco is a brand associated with AADG, Inc., an ASSA ABLOY Group company. Copyright © 2017, AADG, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of AADG, Inc. is prohibited.

**Experience a safer
and more open world**

CEC-151-09/17