

Pemko Product Reference Tech-Spec

Experience a safer
and more open world

XG90KIT_

Excessive Gap Solutions

Example: XG90KIT | 3684 | BL
Profile# Opening Size Finish

TYPE: Self-Adhesive Intumescent with Triple Fin Seal and Galvanized Steel Stop Extender

MATERIAL: PVC Encased Intumescent with Silicone Seal; Galvanized Steel

FINISH (silicone): BL (Black), W (White)

LENGTHS: 48", 84" **OPENING SIZE:** 36x84, 42x84, 48x84 (contact factory for additional sizes)

HSS20XGxS773



WIDTH: 1-3/4" (44.45 mm)

HEIGHT: 7/16" (11.11 mm)

XG900

WIDTH: 1" (25.4 mm)

HEIGHT: 7/16" (11.11 mm)



Product Test Ratings:



Miscellaneous
Fire Door
Accessory

See Product Testing
section for more
information.

LEAD TIME: 7 working days (or less)

AVAILABLE: Shipped from Pemko's Memphis, Ventura, and Toronto locations.

WARRANTY: 2 Years from purchase date, must be installed within 6 months from ship date

CROSS REFERENCE: N/A

INSTRUCTIONS, CAD DRAWINGS, PROFILE DRAWINGS and CUT SHEET

Available upon request and on website

PERFORMANCE INFORMATION

When subjected to temperatures in excess of 300°F this product will expand up to 30 times its original size.

PRODUCT TESTING:

- **UL Classified** – Excessive clearance solutions for door and frame clearances when installed per the manufacturer's instructions, intended for use with UL Classified steel composite, hollow metal doors, wood and plastic covered composite core doors with UL Listed fire door frames up to 1-1/2 hour - up to 3/8".

MATERIAL SAFETY / FIRE HAZARDS

Per OSHA Regulations (Standards – 29 CFR) this Pemko item is considered an “article” as described in section 1910.1200 paragraph (c), meaning that it is a manufactured item other than a fluid and is not a hazard. To help our customers we are providing additional information in this section to cover relevant topics found on Safety Data Sheets (SDS) but not found elsewhere in this document.

FIRE HAZARD:

PVC may emit various toxins when burned, such as hydrogen chloride, carbon monoxide, and other gases. PVC will not normally burn after ignition without an external fire source. Galvanized steel does not present a fire hazard.

FIRST AID MEASURES

Under normal conditions this item presents no small parts and so this item cannot be inhaled or swallowed and has no adverse reaction when coming in contact with skin. Observe good industrial hygiene after installation.

Note to physician: treat symptomatically and supportively

FIREFIGHTING MEASURES

As in any fire, prevent human exposure to fire, smoke, fumes, or products of combustion. Evacuate non-essential personnel from the fire area. Firefighters should wear face mask with self-contained breathing apparatus (SCBA) and impervious protective clothing. In case of aluminum fire, use class D dry powder to extinguish. DO NOT USE water or halogenated extinguishing media.

- Hazardous combustion products: none.

SPILL PROCEDURES

Sweep up any off-cuts from product and store in a suitable container for disposal

HANDLING, STORAGE, AND DISPOSAL

There are no specific handling instructions. Always store at room temperature and keep away from heat sources. When disposing, if possible, recycle the item and its packaging. Otherwise disposal should be in accordance with local, state, or federal legislation. Bury in an authorized landfill site or incinerate under approved controlled conditions.

EFFECTS OF EXPOSURE

There are no effects under normal conditions of use. Observe good industrial hygiene.

TOXICITY

There is no toxicity hazard under normal conditions of use

HEALTH HAZARD

This product may contain hazardous ingredients; harmful effects are unlikely under normal conditions.

CLEANING

Pemko's aluminum products and solid gasket products can be cleaned with a mild soap with warm water. A clean non-abrasive cloth should be used to clean the surface of these products. For removing grease, sealant, or other minimal adhesives a mild solvent such as mineral spirits may be used; then clean with mild soap mixed with warm water. To dry, either allow to air dry or wipe dry with a chamois, squeegee, or lint-free cloth.

For sponge gasket and weatherstrip products, wipe with a damp cloth. Do not use mineral spirits or other chemical as this may cause the plastic to “melt” or deteriorate. To dry, either allow to air dry or wipe dry with a chamois, squeegee, or lint-free cloth.

The use of strong solvents or cleaner concentrations may cause damage to the finish surface and isn't recommended.

MAINTENANCE

Pemko products are generally low-maintenance and require nothing more than general cleaning. Should anything outside of “general cleaning” arise, please consult Pemko Customer Service.

If you have any questions, or if you have a situation outside this scope, please contact Pemko Customer Service.

ASSA ABLOY Opening Solutions
Architectural Door Accessories
orders.pemko@assaabloy.com
www.assaabloydooraccessories.us

Memphis, TN USA
P: 800.824.3018
F: 800.243.3656

Ventura, CA USA
P: 800.283.9988
F: 800.283.4050

Vaughan, ON CA
P: 800.461.3007
F: 800.461.8989