M SERIES EXTRA HEAVY DUTY GRADE 1 LOCK



Small Format IC 6 or 7 pin







Specification

ANSI: Meets ANSI - A156.13, Series 1000, Grade 1 Standards

UL Listed for "A" Label 3 Hour Fire Doors, Singles or Pairs

ADA Compliance: Meets ADA and ANSI A117.1 accessibility codes with lever trim

Lock Case: 2 3/4" Backset with Heavy Gauge Zinc Dichromated Steel

Levers: 5" Full Length cast Zinc

Trim: 2 1/4" x 8 1/8" Cast Escutcheon or 3" Wrought Brass Roses

Lever Return: Independent lever return springs to prevent lever sag

Trim Attachment: Thru bolted Lever or Knob trim for increased security

Handing: Handed as RHR - Easily Rehanded in the field

Armored Front: Wrought Stainless Steel or Brass 1 1/4" x 8"

Latchbolt: Stainless Steel 3 Piece Anti Friction with 3/4" projection

Deadlocking: Non handed Stainless Steel Deadlatch

Deadbolt: 1" Throw, Stainless Steel with a Anti-Saw Pins

Cylinders & Cam: C Keyway 6 pin -11/4" for Sectional & 13/8" for Escutcheon with DH M series cam

Prepared for Small format IC core (less core)

Strikes: 47/8" x11/4" ASA non handed with large rectangular cut out

Stock Trim & Lever: Flat Sectional & Flat Escutcheon (all other levers are special order - 6 week lead time)

Special Order Levers: Curved, Half Curved, Tubular, Ball Knob (special order - 6 week lead time)

Stock Finishes: US26D (all other finishes are special order - 6 week lead time)

Special Order Finishes: US3, US4, US10B, US26, US32, US32D (special order - 6 week lead time)

Electrified Options: Motor Driven lock/unlock function 12/24 V (AC/DC) Fail Safe/Fail Secure

Rex- Request to Exit, LM - Latch Monitor, SM - Security Monitor of latch

Warranty: Limited lifetime warranty





M• 19 x FS x US260 Privacy Indicator



M-32-IND Escutcheo



